
















IT IS RELIABLE!



VS-2112B - 1CH MPEG4/MJPEG Video Server

 <p>MPEG4</p>	 <p>MJPEG</p>	 <p>30 (25) fps</p>		 <p>Rec Motion Detection</p>	 <p>SD Card</p>	 <p>SD Card</p>	
 <p>Software</p>	 <p>NTSC</p>	 <p>PAL</p>	 <p>CE</p>	 <p>FCC</p>	 <p>RoHS</p>	 <p>UPnP</p>	

● SPECIFICATIONS

Model		VS-2112B
Video	Type	BOX TYPE
	System	NTSC / PAL (Automatic detection)
Image	Compression	MJPEG / MPEG4
	Resolution	D1/Half D1/CIF
	Frame rate	30 (25) / 24 / 15 fps, adjustable
	Picture size	MJPEG: 4~64 KB / MPEG4: 64 Kbps ~ 8 Mbps (Bit rate)
	Motion detection	Motion detection (96 zones, 5 levels)
	Time stamp	Time / Date / Title
Audio	8 kHz sample rate, line-in	
Network	Interface	Ethernet (RJ-45 wired, 10/100 base-tx), MDIX supports
	Protocols	TCP/IP, DHCP, HTTP, ICMP, UPnP, ARP, DNS, DDNS, PPPoE, FTP, SMTP
	Throughput	2.0M bytes/sec
Software	Web browser	Microsoft IE 6.0 or above
	PC	Free bundle IP-SURVEILLANCE supports 32 CH recording
	Development tools	ActiveX / HTTP-API / SDK
	Security	Multiple level / Multiple users / IP address filtering
Connectors	Video input	1.0 Vpp, 75 ohm, composite, negative, BNC x 1
	Video output	1.0 Vpp, 75 ohm, composite, negative, BNC x 1
	Alarm I/O/Reset	1 / 1 / 1
	Serial port	RS-485
	SD card	Alarm and schedule recording / update
	USB	Mini type, 1.1 Slave for configuration / update
	Reset	Factory default
Others	LED indicator	Network indicator
	Power requirement	DC12V / 200mA
	Operating temperature	0°C ~ 50°C (32°F ~ 122 °F)
	Dimensions	110 x 60.5 x 32 mm
	Approvals	FCC, CE, RoHS
	Accessories	Power adapter x 1 / User manual x 1 / IP-SURVEILLANCE software x 1 / USB wire x 1
	Update	HTTP / FTP / SD / USB
Hardware	CPU	TI integrated chip
	RAM	64 MB
	Flash	4 MB

*Design and specifications are subject to change without notice.